

## **DECLARATION ACCORDING COMMISSION REGULATION (EU) 2015/1185** April 2015 and **ACCORDING COMMISSION DELEGATED REGULATION (EU) 2015/1186** April 2015

Inform	ation requiren	nents for solid f	uel local spac	ce heat	ers							
Model/Name:				UNICA 10								
Trademark:					NOBIS							
Indirect heating functionality:					No							
Direct heat output:				7,2								
Indirect heat output:												
Fuel:	Preferred fuel:	Other suitable fuel(s):	η₅% (*)			ig emiss at outp	e heating emissions at mum heat output (*)					
				Р	COG		NOX		COG	CO	NOX	
	Vas	No	75.0						mg/Nm <sup>3</sup> (13% O <sub>2</sub> )			
Wood logs with moisture content ≤ 25 %	Yes	No	75,9	8	32	526	74					
Compressed wood with moinsture content < 12 %	No	No										
Chara	cteristics wher	n operating wit	h the preferre	d fuel o	nly							
		Heat output	•									
Nominal heat output:	P <sub>nom</sub>		7,2					kW				
Minimum heat output (indicative):	P <sub>min</sub>		kW									
Will in Horri Hear Corpor (in alcanve).		' min								- KVV		
	Useful eff	ficiency (NCV	as received)									
Useful efficiency at nominal heat output:	$\eta_{\text{th,nom}}$		85,9						%			
Useful efficiency at minimum heat output (indicative)	n <sub>th,min</sub>		%						%			
	Auxiliar	y electricity co	nsumption									
At nominal heat output:		el <sub>max</sub>								kW		
At minimum heat output:	el <sub>min</sub>		kV						kW			
In standby mode:	el <sub>SB</sub>		kW									
	Permanent p	pilot flame pow	er requireme	nt					1			
Pilot flame power requirement:		P <sub>pilot</sub>								kW		
		Single stage h	neat output, n	no room	tempe	erature (	control			No		
	Two or more manual stages, no room temperature control							No				
	With mechanic thermostat room temperature control							No				
Type of heat output/room temperature control F(2):	With electronic room temperature control							No				
	With electronic room temperature control plus day timer							No				
	With electronic room temperature control plus week timer							No				
Other control options F(3) (multiple selections possible):		Room temperature control, with presence detection							No			
		Room temperature control, with open window detection							No			
	With distance control option No											
Energy efficiency class:						<b>Δ</b> +						
Energy efficiency index (EEI):		115										
. , , ,		<u> </u>										

Note:  $(*)\eta_s$  = seasonal energy efficiency, PM = particolate matter, OGC = organic gaseous compounds, CO = carbon monoxide, Nox = nitrogen oxides





## **DECLARATION ACCORDING COMMISSION REGULATION (EU) 2015/1185** April 2015 and **ACCORDING COMMISSION DELEGATED REGULATION (EU) 2015/1186** April 2015

Inform	ation requiren	nents for solid f	uel local spac	ce heate	ers							
Model/Name:				UNICA 10 V / UNICA 10 C								
Trademark:					NOBIS							
Indirect heating fund	ctionality:			No								
Direct heat out	put:			9,3								
Indirect heat output:							-	-				
								I				
Fuel:	Preferred fuel:	Other suitable fuel(s):	η <sub>s</sub> % (*)	Spece heating emissions at nominal heat output (*)  Spece minimum.					e heating emissions at mum heat output (*)			
				P COG CO NOX P					COG CO NOX			
				m	g/Nm³	(13% O	<sup>2</sup> )	n	ng/Nm³	(13% C	) <sup>2</sup> )	
Wood logs with moisture content ≤ 25 %	No	No										
Compressed wood with moinsture content < 12 %	Yes	No	87,1	14,5	3	64	84	15,3	5	94	84	
								ı				
Chara	cteristics wher	n operating wit	n the preferre	d fuel o	nly							
		Heat output										
Nominal heat output:	P <sub>nom</sub>		9,3					kW				
Minimum heat output (indicative):	P <sub>min</sub>				kW							
	Useful ef	ficiency (NCV a	as received)							~		
Useful efficiency at nominal heat output:	$\eta_{th,nom}$		90					%				
Useful efficiency at minimum heat output (indicative)	N <sub>th,min</sub>		91					%				
	Auxiliar	y electricity co	nsumption									
At nominal heat output:	el <sub>max</sub>		0,055					kW				
At minimum heat output:	el <sub>min</sub>		0,014						kW			
In standby mode:	$el_{SB}$		0,008 kW									
	Permanent	pilot flame pow	er requireme	ent								
Pilot flame power requirement:	P <sub>pilot</sub>							kW				
normaline power requirement.		· piloi								K//		
	Single stage heat output, no room temperature control											
	Two or more manual stages, no room temperature control							No				
Type of heat output/room temperature control F(2):	With mechanic thermostat room temperature control							No				
Type of field output/footh temperature control F(z):	With electronic room temperature control							No				
	With electronic room temperature control plus day timer							No				
	With electronic room temperature control plus week timer								Yes			
	Room temperature control, with presence detection No											
Other control options F(3) (multiple selections possible):		Room temperature control, with open window detection							No			
		With distance control option							Yes			
Energy efficiency class:		A+										
Energy efficiency index (EEI):		128										

**A** 



Note:

(\*)Ns = seasonal energy efficiency, PM = particolate matter, OGC = organic gaseous compounds, CO = carbon monoxide, Nox = nitrogen oxides